

TRAFFIC CONTROL FOR CORING OF HOT BITUMINOUS PAVEMENT

D-704-2

TWO LANE, TWO WAY ROADWAYS


MULTILANE ROADWAY

Notes


- 1. The working vehicle shall display a 360 degree flashing or rotating beacon.
- 2. The protection vehicle shall display a 360 degree flashing or rotating beacon. Two high intensity flashing lights mounted on the rear adjacent to the sign.
- 3. A flagger shall be used to protect the work area and warn oncoming traffic.
- 4. This application is for use during daylight hours and in areas of good visibility only.

Notes


- 1. The working vehicle shall display a 360 degree flashing or rotating beacon.
- 2. The shadow vehicle shall display a 360 degree flashing or rotating beacon, a Sequencing Arrow Panel Type C, operated in the chevron mode.
- 3. This application is for use during daylight hours and in areas of good visibility only.



Typical Protection vehicle



Typical Protection Vehicle



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION		This document was originally issued and sealed by MARK S GAYDOS, Registration Number PE-4518, on 12/01/04 and the original document is stored at the North Dakota Department of Transportation
03-01-90		
REVISIONS		
DATE	CHANGE	
06-02-90 11-10-93 06-06-95  08-15-96 07-04-97 12-01-04	Signs Flag note Typical shadow vehicle & flag note Revise flag note General revisions PE stamp added	